

ST JOHN'S ROAD

NOTES:

- 1. THE LAYOUT IS SUBJECT TO DETAILED DESIGN,
 CAPACITY TESTING, GROUND INVESTIGATIONS RESULTS
 & EARTHWORKS MODELLING, UTILITIES & SERVICES
 AND CONFIRMATION OF LAND OWNERSHIP;
- 2. THE DETAILED DESIGN LAYOUT WILL BE DESIGNED IN ACCORDANCE WITH ALL RELEVANT DESIGN GUIDANCE AND STANDARDS:
- 3. THE LAYOUT HAS BEEN BASED ON THE APPROPRIATE DESIGN SPEED FOR OUR CURRENT PROPOSALS:
- 4. THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH ALL RELEVANT ASSOCIATED DOCUMENTS;
- 5. THE USE OF THE DRAWING DOES NOT ABSOLVE THE CLIENT FROM THEIR RESPONSIBILITIES IN REGARDS TO HEALTH & SAFETY AND CDM REGULATIONS;
- 6. THE DESIGN HAS BEEN BASED ON OS DATA AND THEREFORE REQUIRES CONFIRMATION WITH A TOPOGRAPHICAL SURVEY; AND
- 7. SUBJECT TO REVIEW AND COMMENTS FROM THE LOCAL HIGHWAY AUTHORITY.

KEY:

EXTENT OF HIGHWAY LAND MAINTAINED AT PUBLIC'S EXPENSE. INTERPRETED FROM GLOUCESTERSHIRE PLAN DATED 20/09/19

EXTENT OF LAND WITHIN CLIENT'S CONTROL

| Α | UPDATED THROUGH DESIGN PROCESS | 15.07.21 | JW | JB | JB |
|------|--------------------------------|----------|-------|------|------|
| Mark | Revision | Date | Drawn | Chkd | Appd |
| | | | | | |

SCALING NOTE: <u>Do not</u> scale this drawing - any errors or omissions shall be reported to Stantec without delay.

UTILITIES NOTE: The position of any existing public or private sewers, utility services, plant or apparatus shown on this drawing is believed to be correct, but no warranty to this is expressed or implied. Other such plant or apparatus may also be present but not shown. The Contractor is therefore advised to undertake their own investigation where the presence of any existing sewers, services, plant or apparatus may affect their operations.

Drawing Issue Status

CONCEPT

WISLOE NEW SETTLEMENT PROPOSED ACCESS STRATEGY RIGHT TURN LANE AT SOUTHERN A38 FRONTAGE

Client

DURSLEY I

GCC & ERNEST COOK TRUST

| | Date of 1st Issue 11.05.21 | Designed SL | Dra | awn SL |
|---|-------------------------------|----------------|-----|-----------|
| l | A3 Scale 1:1000 | Checked JB | | |
| | Drawing Number | | | Revision |

Drawing Number 332310150/5501/SK02 Rev





stantec.com/uk


Copyright reserved ne copyrights to all designs and drawings are the property of Stantec Reproduction or use for any purpose other than that authorised by Stantec is forbidden.


el: 01823 218 940


191






















Appendix C Non Motorised User M5 Bridge Feasibility Report



THIS PAGE IS LEFT INTENTIONALLY BLANK FOR DOUBLE SIDED PRINTING



Wisloe New Settlement

Non-Motorised User Route Over M5 - Feasibility Report

On behalf of Ernest Cook Trust & Gloucestershire County Council



Project Ref: 332310150 | Rev: P01 | Date: May 2021





Contents

| 1 | Introd | Introduction | | | | |
|-------|------------|---|---|--|--|--|
| | 1.1 | Overview | 1 | | | |
| | 1.2 | Consultations and requirements | 1 | | | |
| | 1.3 | Geology | 2 | | | |
| | 1.4 | Loading | 2 | | | |
| | 1.5 | Environment | 2 | | | |
| | 1.6 | Land and Property | 2 | | | |
| 2 | Bridg | e Feasibility | 3 | | | |
| | 2.1 | Description of proposed structure options | 3 | | | |
| | 2.2 | Capital cost and whole life cost | 3 | | | |
| | 2.3 | Appearance | 4 | | | |
| | 2.4 | Sustainability and use of natural resources | 4 | | | |
| | 2.5 | Durability / design life | 5 | | | |
| | 2.6 | Health and safety, and potential risks and constraints to the project | 5 | | | |
| | 2.7 | Proposed design method | 5 | | | |
| | 2.8 | Departures from standards | 5 | | | |
| | 2.9 | Construction issues | 5 | | | |
| | 2.10 | Operation and maintenance | 5 | | | |
| | 2.11 | Preferred option | 5 | | | |
| | 2.12 | Proposed category of check | 6 | | | |
| | 2.13 | Role of the works examiner supervising the works | 6 | | | |
| Tak | oles | | | | | |
| Table | e 2.1 – Oı | ption 1 Costs | 4 | | | |
| | | ntion 2 Costs | | | | |

Appendices

Appendix A Option Drawings



THIS PAGE IS LEFT INTENTIONALLY BLANK FOR DOUBLE SIDED PRINTING



1

1 Introduction

1.1 Overview

- 1.1.1 Stantec was instructed by Gloucestershire County Council and the Ernest Cook Trust as the landowners of the site to consider the potential to provide a non-motorised user (NMU) link by way of a bridge between their proposed mixed use residential led scheme known as Wisloe New Settlement and Cam & Dursley Railway Station. To connect the two this link would therefore need to cross the M5 which falls within the control of Highways England.
- 1.1.2 This report considers two options:
 - Option 1 Foot/cycle bridge fully spanning M5 and Highways England land located either side
 - Option 2 Foot/cycle bridge with minimum span over existing M5 carriageway.
- 1.1.3 Discounted options and reasons include:
 - Underpass discounted due to topography, NMU experience and disruption to the travelling public on the M5
 - 3 span bridge, adding backspans over adjacent land to create a more open structure and reduce the volume of earthworks.
- 1.1.4 A location plan is included in the option drawings in Appendix A.
- 1.1.5 Headings in this report follow the heading requirements and guidance for a structures option report in line with current Highways England requirements, as laid out in Appendix O of standard CG 300 in the Design Manual for Roads and Bridges (DMRB). Although the current feasibility study does not form a full structures options report, the structure is provided to allow for further development work.

1.2 Consultations and requirements

- 1.2.1 The main technical requirements are set out in the DMRB published by Highways England. This includes requirements to design to standards published by the British Standards Institution including the Eurocodes.
- 1.2.2 Stantec's transport planning team consulted both Highways England and Gloucestershire County Council in their role as the strategic highway and local highway authority respectively. This led the former to confirm their in principle support for a foot/cycle bridge with the only proviso being that the structure would need to have a clear span across the motorway. Similarly, the local highway was also supportive particularly given it emerged at the time that they were planning to submit a funding bid for a foot/cycle bridge across the M5 at more or less the same location.
- 1.2.3 Stantec in their role as the transport planning consultant for the site requested that the bridge have compliance with Local Transport Note (LTN) 1/20 Cycle Infrastructure Design, the key impact of which is requiring a clear width of 5.5m. This is significantly wider than the DMRB minimum requirement in CD 353 for a width of 3.5m and results in the introduction of a site splice joint along the centre of the bridge.



1.3 Geology

- 1.3.1 British Geological Survey (BGS) Geology of Bridge viewer indicates that the geology consists of Cheltenham Sand and Gravel superficial deposits overlying Blue Lias Formation and Charmouth Mudstone Formation (undifferentiated) Mudstone.
- 1.3.2 There are three nearby historical borehole scans available on the BGS website.

1.4 Loading

- 1.4.1 The feasibility report is based on achieving a standard footbridge headroom of 5.7m over the M5. The Department for Transport (DfT) Heavy and High Routes map does not show the M5 at this location as a high load route.
- 1.4.2 Foot/cycle bridge structural loading will be in accordance with the Eurocodes and the DMRB.

1.5 Environment

1.5.1 No environmental requirements or constraints are known at this time.

1.6 Land and Property

1.6.1 The land considered either side of the M5 to accommodate a bridge is within the control of the landowners.

2



2 Bridge Feasibility

2.1 Description of proposed structure options

- 2.1.1 Proposed options are:
 - Option 1 Single 58m square span over M5 bow arch truss bridge
 - Option 2 Single 42.6m square span over M5 bow warren truss bridge.

2.2 Capital cost and whole life cost

- 2.2.1 Exclusions:
 - Land costs
 - Survey costs topographical and ground investigation
 - Legal and professional costs
 - Highway Authority adoption costs (commuted sums)
 - Contract administration and works examination costs
 - Enabling works
 - Contractor's preliminaries, overhead and profit
 - Traffic Management
 - Deep foundation if required
 - Earthworks
 - Drainage
 - Streetlighting
 - Hard and soft landscaping
 - Parapets and fencing on approach to bridge
 - Vehicle Restraint Systems (VRS) on the motorway
 - Other aspects of approaches to bridge.
- 2.2.2 The costing is indicative and has been based on engineering experience of similar highway structures where Stantec have been involved. It should be noted that Stantec are not cost consultants. No bridge scheme is identical to another, bridges are often bespoke to the constraints they address. Constraints discovered during further design stages may have a significant effect on the costs. It should also be noted that steel and other construction material prices are highly volatile.



Option 1 - Single 58m square span over M5 bow arch truss bridge

| Element | Quantity | Unit | Rate (£) | Budget Cost (£) |
|---|--------------------|----------------|----------|------------------------|
| Superstructure Steelwork Deck Plan Area | 5.5 x 58 = 319 | m² | 3,500 | 1,116,500 |
| Substructure – Abutment Elevation Area | 2 x 190 = 380 | m² | 200 | 76,000 |
| Substructure - Bankseats | 2 x 7 x 1 x 1 = 14 | m ³ | 400 | 5,600 |
| Total | | | | 1,198,100 round to: |
| | | | | 1,200,000 |

Table 2.1 – Option 1 Costs

Option 2 - Single 42.6m square span over M5 bow warren truss bridge.

| Element | Quantity | Unit | Rate (£) | Budget Cost (£) |
|---|----------------------------------|----------------|----------|----------------------|
| Superstructure Steelwork Deck Plan Area | 5.5 x 42.6 = 234 | m² | 3,500 | 819,000 |
| Substructure – Abutment Elevation Area | (52+196x2) + (52+150x2) = 796 | m ² | 200 | 159,200 |
| Substructure - Bankseats | 2 x 7 x 1 x 1 = 14 | m ³ | 400 | 5,600 |
| Total | | | | 983,800 round to: |
| | | | | 1,000,000 |

Table 2.2 – Option 2 Costs

2.2.3 Whole life cost to be considered at a future design stage.

2.3 Appearance

2.3.1 The appearance will be considered by the landscape architect, the broader client team and the Local Planning Authority.

2.4 Sustainability and use of natural resources

2.4.1 Most steel is recycled at its end of life and the bridge steelwork will contain the standard proportion of recycled steel in line with the current supply of steel. At the end of its service life the steel will be recycled.



- 2.4.2 Concrete elements such as the substructure will be able to use cement replacements such as ground granulated blast furnace slag. At the end of its service life the concrete can be crushed and used as an engineered fill.
- 2.4.3 Where reinforced soil is used, this reduces the use of natural earthworks fill material.

2.5 Durability / design life

- 2.5.1 The structure with be designed with a 120 year design life.
- 2.5.2 The structure will be designed to be low maintenance and will consider options of emerging paint coating technology which may be able to increase the interval between repainting.
- 2.5.3 Water will be managed by collecting the run-off from the bridge into positive drainage system located off the bridge deck.

2.6 Health and safety, and potential risks and constraints to the project

2.6.1 No unusual hazards and risks identified to date.

2.7 Proposed design method

2.7.1 To be confirmed at future stage of design.

2.8 Departures from standards

- 2.8.1 If piled foundations are required a Departure from Standard is required to use the latest ICE Specification for Piling and Embedded Retaining Walls, as this has been updated for use with Eurocodes whereas the Specification for Highway Works has not yet been updated.
- 2.8.2 Foot/cycle bridge deck waterproofing is an aspect not covered by standards and would require consideration via the departures from standards system.
- 2.8.3 Consideration may be given to the use of a more durable paint coating system than the standard systems currently in the Specification for Highway Works.
- 2.8.4 No other departures are anticipated.

2.9 Construction issues

2.9.1 A full closure of the M5 will be required for installation of the superstructure bridge deck. The standard diversionary route via the A38 will be required between Junctions 13 and 14 of the M5.

2.10 Operation and maintenance

2.10.1 No unusual methods or facilities required for carrying inspections and maintenance.

2.11 Preferred option

2.11.1 To be confirmed in consultation with the client and highway authorities prior to next stage of work.



2.12 Proposed category of check

- 2.12.1 Check to be undertaken:
 - Option 1 Category 3 due to span
 - Option 2 Category 2

2.13 Role of the works examiner supervising the works


- 2.13.1 To be confirmed at future stage of design.
- 2.13.2 The CG 300 template includes text for submission by the designer to Highways England as Technical Approval Authority and agreement by the same. This has been omitted at this stage of the design development.





Appendix A Option Drawings




THIS PAGE IS LEFT INTENTIONALLY BLANK FOR DOUBLE SIDED PRINTING













TAUNTON

Lakeside House, Blackbrook Business Park, Blackbrook Park Avenue, Taunton TA1 2PX

Tel: +44 1823 218 940 www.stantec.com/uk

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or amissions shall be reported to Stantec without delay, - the Copyrights to all designs and chawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.

UTILITIES NOTE: The position of any existing public or private sewers, utility services, plant or apparatus shown on this drawing is believed to be correct, but no warranty to this expressed or implied. Other such plant or apparatus may also be present but not shown. The Contractor is therefore advised to undertake their own investigation where the presence of any existing sewers, services, plant or apparatus may affect their operations.

THIS DRAWING IS BASED UPON PRELIMINARY DATA AND IS FOR ILLUSTRATIVE PURPOSES ONLY

ALL DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE.

0100.3 ALL LEVELS ARE IN METRES AND RELATIVE TO ORDNANCE DATUM (NEWLYN). ALL LEVELS ARE IN METRES AND RELATIVE TO ORDNANCE DATUM (NEWLYN).

THIS DRAWING IS BASED UPON THE FOLLOWING SUPPLIED DIGITAL

INFORMATION.

ONLY AND DATABASE RIGHTS.

CONTAINS ORDNANCE SURVEY DATA @ CROWN COPYRIGHT AND

DATABASE RIGHT SURVEY DATA @ CROWN COPYRIGHT AND

DATABASE RIGHT SURVEY DATA BASE RIGHTS 2021 ORDNANCE SURVEY
010031673.

LANDSCAPE ARCHITECTS PLAN: Drg. REFERENCE: M5 bridge sketch
options.dwg

0100.5 THE GEOMETRY DEPICTED IN THIS DRAWING HAS BEEN DETERMINED FROM THE FOLLOWING:

• THE DEPARTMENT FOR TRANSPORTATION / HIGHWAYS FAIGH AND DESIGN.

- E FOLLOWING:
 THE DEPARTMENT FOR TRANSPORTATION / HIGHWAYS ENGLAND DESIGN
 MANUAL FOR ROADS AND BRIDGES.
 DEPARTMENT FOR TRANSPORT: CYCLE INFRASTRUCTURE DESIGN
 DOCUMENT LTN1/20.

| PO1 FIRST ISSUE | | GCP | SCW | 2021.05.12 |
|-----------------|------|-------|-------|------------|
| Issued/Revision | | Ву | Appd | YYYY.MM.DD |
| | | | | |
| | GCP | GCP | SCW | 2021.05.12 |
| | Dwn. | Dsgn. | Chkd. | YYYY.MM.DD |
| | | | | |

Issue Status

INFORMATION

This document is suitable only for the purpose noted above.
Use of this document for any other purpose is not permitted.

Client/Project Logo

Client/Project

GCC & ERNEST COOK TRUST

WISLOE NEW SETTLEMENT

NMU ROUTE OVER M5

BRIDGE FEASIBILITY OPTION 1

Project No. 332310150 (50753) Scale 215 As Indicated

Revision

Drawing No. 332310150-STN-SBR-NMU-DR-CB-0001

P01

